



Manual



Controller DMX
SimpleDesk 24

Table of contents

1. Safety instructions	3
1.1. Instructions for a safe and efficient operation.....	3
1.2. Further safety instructions	4
1.3. Designated use.....	4
2. Introduction.....	6
3. Connections	6
3.1. Electrical connections.....	6
3.2. DMX connections	6
4. Control.....	7
5. Technical data	7

1. Safety instructions



- This Device is suitable for indoor use only.
- All modifications will void the warranty.
- Repairs have to be carried out by skilled personnel only.
- Only use fuses of the same type and original parts as spare parts.
- Protect the Unit from rain and humidity to avoid fire and electric shocks.
- Make sure to unplug the power supply before opening the housing.

1.1. Instructions for a safe and efficient operation

Please read careful through this manual before the first start-up.

All persons which are entrusted with installation, start-up, operation, maintenance and repair of this device have to:

- Show a corresponding competence.
- Follow the lines of this manual.
- Face this manual as part of the product.
- Keep this manual over the lifetime of the product.
- Pass this manual to new owners of the device.

Be careful with heat and extreme temperature.

Only use the device in a place where no extreme temperatures will occur.

Do not keep it in a temperature bellow 32°F (0°C), or exceeding 104°F (40°C).

Avoid exposing it to direct rays of the sun or near a heating appliance.

You have to attend that with an ambient temperature von 40°C it is not allowed that the relative humidity exceeds 50%.

Keep away from humidity; water and dust.

Do not place it in a location with high humidity or lots of dust.

Containers with liquid should not be placed on or near the device.

Avoid placing it on un-stable location

Select a level and stable location to avoid vibration.

Do not use chemicals or volatile liquids for cleaning

Use a clean dry cloth to wipe off the dust. Metal Parts can be cleaned with a wet soft cloth for stubborn dirt. Before cleaning the device makes sure you disconnect the power plug.

If out of work, contact sales agency soon.

If any trouble occurs, remove the power plug immediately, and contact with an engineer for repairing, do not open the cabinet by yourself; it might result in a danger of electric shock.

Take care with the power cable.

Never pull the power cable to remove the plug from the receptacle, be sure to hold the plug itself.

Make sure that it isn't possible to squeeze or damage the power cable with sharp edges. Assure yourself with regular checks that there are no damages to the power cable or the device itself.

When not using the device for an extended period of time, be sure to disconnect the plug from the receptacle.

IMPORTANT:

Damages caused by the disregard of this user manual are not subject to warranty. The dealer will not accept liability for any resulting defects or problems. Make sure the electrical connection is carried out by qualified personnel. All electrical and mechanical connections have to be carried out according to the European safety standards.

1.2. Further safety instructions

**IMPORTANT!**

**Handle with the dangerous electric voltages carefully.
With this voltage there is the danger to get a life-threatening electric shock.**

After taken the device from a cold room to a warm room, it is not allowed to activate the device. It is possible that thereby emerged condensed water damages the device. Do not activate the device until it reached ambient temperature.

Make sure that the voltage which it is connected to does not exceed the specified values.

Don't switch the device in short time intervals (e.g. in second cycle) on or off.

Keep away children and laymen off the device.

**Health risk!**

Don't look directly into the light source. At certain circumstances it is possible that some people get epileptic seizures. This is especially true for individuals whose epilepsy was determined by a doctor.

1.3. Designated use

This device was developed for professional use on stages, in discos, theatres etc. The device is only approved for a connection up to 230V 50/60 Hz AC voltage.

Regular breaks during operation increase the lifetime of your device.

Avoid vibrations or any form of forceful impact during the installation, the start-up or Operation of the device.

Make sure that the device is not exposed excessive heat, humidity or dust at the place of installation.

Take care that no cables are lying around. You would endanger your own safety and also the safety of a third party.

It is not allowed to operate or store the device in an environment in which spray water, rain, humidity or fog is expected. Humidity or very high atmospheric humidity could reduce the isolation of the device and could cause deathly electric shocks. If you use fog devices the device may not be exposed to a direct smoke jet. There has to be a safety distance of at least 0.5m between this device and the fog machine. Make sure that the saturation of the fog has to enable a visibility of at least 10m.

Do not operate the device during thunderstorms. Surge voltages could destroy the device. Unplug the device from the power supply during thunderstorms.

Surrounding objects or surfaces should not be in contact with the device.

The device has to be protected by a suitable safety cord.

Make yourself familiar with the functions of the device before start-up. People without the experience should not handle the device. The most cause of functional disorder is inappropriate handling.

Use the original packing or designated accessory for transport to avoid damages.

For reasons of safety unauthorized changes are forbidden.

A usage of the device which differs from usages which are described in this manual can cause damages of the device. In that case the warranty expires. Additional you should notice that every differed usage is related with dangers and can cause e.g. an electrical short, fire, electric shock or crash.

2. Introduction

Thank you for buying the **Controller DMX SimpleDesk 24**. It is a powerful device.
For a successful installation and operation, please read this manual carefully.

3. Connections

3.1. Electrical connections

If you wish to change the power supply settings, see the chapter Appendix. Connect the fixture to the mains with the enclosed power cable and plug. The earth has to be connected.

Cable (EU)	Cable (US)	Pin	International
Brown	Black	Live	L
Light blue	White	Neutral	N
Yellow/Green	Green	Earth	

3.2. DMX connections

To make a DMX512 connection go ahead like it is described in the picture. Make sure that you use shielded cable. 3-pin or 5-pin XLR cables are suitable.

If you use a controller with 5-pin DMX output, you need to use a 5-pin to 3-pin adapter.

4. Control

The **DMX SimpleDesk 24** can control up to 24 DMX circuits. Connect the device as described. If you push the fader up, the **DMX SimpleDesk** will output the corresponding value.

Each fader has a resolution of 8 bits.

The DMXin allows you to connect additional DMX controller to control more channels or to obtain a general average solution.

If the **DMX SimpleDesk 24** gives out the DMX addresses 1-24 and a second controller, e.g. 25-48, the signal will be carried out without being changed.

If the DMX areas of both controllers are overlapping, e.g. both controller are set to channels 1-24, the setting of the controller which has been changes at last will be give out.

5. Technical data

Power supply	
Voltage	110-240 V; 50/60 Hz
Connections	
XLR in/out	3pol Neutrik
Controlling	
DMX512	Yes
Number of channels	24
Hardware	
Dimensions	482 x 133 x 82 mm
Weight	2,90 kg

Importer:

B & K Braun GmbH
Industriestraße 2
D-76307 Karlsbad
www.bkbraun.com
info@bkbraun.com

